



## ROVER P4 OIL FILTER ADAPTOR FITTING INSTRUCTIONS

**Please** read all the instructions before starting work on your car.

This kit is suitable for the Rover P4 engine where the **solid central bolt** comes up through the filter into the filter head. The kit contains:

- Flat rubber seal
- O-ring
- Aluminium adaptor plate
- Adaptor bolt
- Cannister bolt
- Oil filter



*(This diagram is for illustration purposes)*

Remove the bowl which contains the original oil filter element and place to one side. Remove the old rubber seal which sits in the groove in the filter head. This may be difficult to see and it often seems as though there is no seal as they become hard and compressed with age, but it is important to replace this seal in order to ensure a leak-proof installation.

Fit the new seal supplied with this kit, making sure that the seal sits correctly in the groove. Fit the smaller rubber o-ring into the boss in the centre of the adaptor plate. Position the plate on the filter head with the o-ring uppermost and then insert the adaptor bolt through the plate and screw the bolt into the filter head until it is finger-tight. Using a 1" AF socket tighten the adaptor bolt fully.

You can now use a modern spin-on filter on your Rover. We recommend a Crosland 2022 or similar high quality filter. Remember to lubricate the sealing ring on the filter and fill the filter with fresh oil before fitting. Observe the original filter change intervals. Always check for oil leaks after fitting a new filter.

Also available for all Rovers : braided stainless steel brake and clutch hoses, fuel lines, oil coolers, petrol filters. Ask for details.